


NEON EDGE | WHITE



COLOUR	CODE
WARM WHITE 2700 K +/- 150 K	BL-LS-4000-27
NATURAL WHITE 4000 K +/- 275 K	BL-LS-4000-40
COOL WHITE 5000 K +/- 300 K	BL-LS-4000-50

SOLD BY THE METRE
IES FILES AVAILABLE

APPLICATION

- Cove lighting, handrails or toeckicks
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

FEATURES

- UV and flame resistant
- Suitable for use around salt or chlorinated water

TECHNICAL DATA


LED WATTS	12 W/m
INPUT VOLTS	24 V
OPERATING TEMP	- 20 °C ~ + 45 °C
MAX. RUN PER POWER FEED	10 m using a single connector 20 m using both connectors (IP 40 sleeve or IP 65 screw connectors 01 & 02)
CRI (Ra)	> 80
LUMENS	380 lm/m
BEAM ANGLE	160°

SOURCE LIFE	50,000 hours
WARRANTY	2 years
BEND RADIUS	120 mm
DIMENSIONS	W 11.5 mm x H 21 mm
INGRESS PROTECTION	Protection is established by either IP 40 or IP 65 accessories
LED PITCH	16.7 mm
CUTTING LENGTH	100 mm
HOUSING	White UV and flame resistant PVC
CONTROL	Dimmable by PWM signal

IP 40 ACCESSORIES



BL-LS-4011
BL-LS-4012



BL-LS-4002




BL-LS-4013

ACCESSORIES	CODE
SLEEVE CONNECTOR 01 IP 40, 1 M CABLE	BL-LS-4011
SLEEVE CONNECTOR 02 IP 40, 1 M CABLE	BL-LS-4012
SLEEVE END CAP IP 40	BL-LS-4002
300 MM FLEXIBLE CONNECTOR IP 40	BL-LS-4013

SUITABLE FOR INDOOR APPLICATIONS

IP 65 ACCESSORIES




BL-LS-4007
BL-LS-4008



BL-LS-4001



BL-LS-4009




BL-LS-4010

ACCESSORIES	CODE
SCREW CONNECTOR 01 IP 65, 1 M CABLE	BL-LS-4007
SCREW CONNECTOR 02 IP 65, 1 M CABLE	BL-LS-4008
SCREW END CAP IP 65	BL-LS-4001
300 MM FLEXIBLE CONNECTOR IP 65	BL-LS-4009
INLINE CONNECTOR IP 65	BL-LS-4010

SUITABLE FOR OUTDOOR APPLICATIONS
IP68 PRODUCT AVAILABLE UPON REQUEST

MOUNTING


ACCESSORIES	CODE
SELF-LOCKING ALUMINIUM PROFILE 2 M	BL-LS-4003
SELF-LOCKING ALUMINIUM MOUNTING CLIP	BL-LS-4004
PLASTIC PROFILE 500 MM	BL-LS-4005
PLASTIC PROFILE 1 METRE	BL-LS-4006



BL-LS-4003



BL-LS-4004



BL-LS-4005
BL-LS-4006