


FINO583 MEDICO | 600 x 600 LED PANEL







FEATURES

- Cyanosis Observation Index (COI) compliant with AS/NZS 1680.2.5:1997
- High performance COB and high CRI (Ra >90)
- High uniformity with wide beam distribution
- Glare-free and shadow-free illumination
- Slim design featuring narrow aluminium silver frame with matte opal diffuser
- Fully dimmable 1-10V and DALI driver
- Easy installation for T-bar ceiling systems

APPLICATIONS

• Suitable for health and care. Hospitals, schools and offices.

UGR = <19 - c0-c180 - c90-c270



DIMENSIONS

595 mm (L) x 595mm (W) x 8.6mm (H)

FINISH

Anodised aluminium with high efficiency opal polystyrene diffuser. Special powdercoat on request.

MOUNTING

For standard metric T-Bar ceiling recessed installation. Plaster ceiling recessed installation kit, suspension installation kit and surface mounting installation kit also available.

TECHNICAL DATA

LED CHIP	Osram Cyanosis LED chip	BASE	(±10%) AC
LED QTY	112 pcs	SOURCE LIFE	50,000 hours L70
POWER CONSUMPTION	42W	INPUT VOLTAGE	90 ~ 264 VAC
COLOUR TEMP	4000K	FREQUENCY	50/60 Hz
CRI (Ra)	≥90	DIMENSIONS	595 mm (L) x 595mm (W)
ССТ	3721 ± 40 K		x 8.6mm (H)
COI	2.8 ± 0.3	WEIGHT	3160 g
EFFICACY	100 lm/Watts	PROTECTION RATING	IP44 (on room side)
DIMMABLE	1-10V DALI	UGR	<19