



### FEATURES

- CNC Machined wall bracket
- Hollow wall bracket to conceal the power supply
- Low voltage input makes hanrail safe to touch
- Remote driver options range from 24V DC 30W to 24V DC 320W.

### APPLICATIONS

- Residential and commercial staircases
- Thoroughfares
- Indoor and outdoor applications

### RECOMMENDED LED STRIP

- 4W 3000K – 280 lumens per metre – NOT DOT-FREE
- 4W 4000K – 320 lumens per metre – NOT DOT-FREE
- 9W 3000K – 610 lumens per metre
- 9W 4000K – 756 lumens per metre
- 13W 3000K – 890 lumens per metre
- 13W 4000K – 1020 lumens per metre

Opal diffusers provide “dot-free” lighting with all LED strip options above except for 4W.

All LED strip options above are also available in IP65. Please note that IP65 LED strips may not provide “dot-free” lighting in this product.

Lumen outputs stated above are for the bare LED strip – opal or satin diffusers reduce lumen figures by approximately 55%. Clear diffusers reduce lumen figures by approximately 35%.

Please contact Buckford Illumination Group for more LED strip and driver information.

Phone: (+61) 3 9646 8201

Email: [info@buckford.com.au](mailto:info@buckford.com.au)

### DIMENSIONS

Width 50 mm x height 17 mm

### FINISH

Anodised aluminium with polycarbonate diffuser.  
Special powder-coat on request.

### MOUNTING

Mounting Bracket