
## **LCB LIBRA 311**







## **FEATURES**

- Industrial plastic and aluminium made body
- Integrated pure aluminium heatsink
- PC reflector processed through vacuum aluminium plating
- Suitable for accent lighting applications such as auto show and jewelry display Adjustable mid-ring provides ± 30° projection angle Efficient heat dissipating pillar made in 1070 pure aluminium

- High performance COB and high CRI (Ra > 80)
- Cylindrical radiator, cooling efficiency is greatly improved

18 W

## **TECHNICAL DATA**

**LED WATTS** 

OPERATING TEMP	- 25 °C <b>~</b> + 40 °C	CUTOUT	Ø 95 mm
CRI (Ra)	≥ 80	LED BRAND	COB
COLOUR TEMP	2700 K   3000 K   4000 K	COLOUR	White   Silver   Black
LUMENS	1050 lm	PROTECTION RATING	IP 20
BEAM ANGLE	15°   30°	DIMMABLE	Dimmable by phase control
SOURCE LIFE	50,000 hours L70		(Trailing edge only) from approved dimmers

**DIMENSIONS** 

Ø 104 mm x 91 mm

## **PRODUCT CODES**

Product Family - Power - Beam Angle - Colour Temperature - Colour

Example:

LCB LIBRA 311 - 7W - 24 - 3000K - WH